

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

- 1.Contact current Rating:5 Amperes.
- 2.Insulation Resistance:1000 Megohms Minimum.at DC 500V
- 3.With stand voltage : 1000V AC RMS for 1Minute
- 4.Contact Resistance:30 Milliohms Maximum
- 5.Operating Temperature:-25°C to +85°C

※ SIGN "X" IS IMPORTANCE DIMENSION

PART NO:

KDSA1-15 F -1 N X-X

PIN:
15極性:
F:母座鍍金厚度:
1:G/F鐵殼電鍍:
N:鍍

螺絲:

O:叉鎖螺絲
N:鉚鎖不附螺絲
Y:鉚鎖螺絲
F:鉚附螺絲塑膠:
B:BLACK
L:BLUE
G:GRAY





螺丝

⑦	RIVET	2	BRASS	Ni
⑥	COVER	1	PBT+30%G/F	BLUE/BLACK/GRAY
⑤	SCREW	2	STEEL	Ni
④	FISH FORK	2	SPCC	Tin
③	SHELL	1	SPCC	Ni
②	CONTACT	15	BRASS	GOLD FLASH
①	INSULATOR	1	PBT+30%G/F	BLUE/BLACK/GRAY
ITEM	PART NAME	QTY.	MATERIAL	REMARKS

KEM 奇速科技有限公司
Qi-Speed Technology CO., LTD.

產品名稱:
PRODUCT NAME
D-SUB 90° 15PIN 母座 3.08mm

單位: mm	繪圖	設計	審核	核准	料號:KDSA1-15F-1NX-X
比例:	DRAWING	DESIGNED	CHECKED BY	APPROVAL BY	PART NUMBER
公差: .X ±0.38 .XX ±0.25 .XXX ±0.20	JOHNY	JOHNY	LUKE	JAMES	圖號:KDSA1-15F-1NX-X-1 DRAWING NO
日期: 2010/6/10					版本: REV. 0

O: 叉鎖螺絲	N: 鉚鎖不附螺絲	Y: 鉚鎖螺絲	F: 鉚附螺絲
			

版本	修改事項	修改日期
----	------	------