

NOTE:

1.MATERIAL:

Rated voltage : 40 VAC

Rated Current : 5AMP

Contact Resistance : 30m Ω MAX.Insulation Resistance : 1000M Ω MIN.at 500V DC

Withstanding voltage : 500V AC RMS for 1Minute

Temperature range : -25C°- +85C°

※ SIGN “(X)” IS IMPORTANCE DIMENSION

PART NO:

KDSA5-XX F -1 N X-X

PIN:

09/15/25/37

極性:

F:母座

鍍金厚度:

1:G/F

鉄殼電鍍:

N:鍍

塑膠:

B:BLACK

L:BLUE

螺絲:

O:叉鎖螺絲

N:鉚合不附螺絲

F1:鉚附鐵螺絲4.8*11.8

F2:鉚附鐵螺絲5.8*12.8

F3:鉚附銅螺絲4.8*11.8

F4:鉚附銅螺絲5.8*12.8

Y1:鉚鎖鐵螺絲4.8*11.8

Y2:鉚鎖鐵螺絲5.8*12.8

Y3:鉚鎖銅螺絲4.8*11.8

Y4:鉚鎖銅螺絲5.8*12.8

⑦	Screw	2	SPCC	Ni
⑥	RIVET	2	COPPER ALLOY	Ni
⑤	COVER	1	PBT+30%G/F	BLACK
④	FISH FORK	2	SPCC	TIN
③	SHELL	1	SPCC	Ni
②	CONTACT	9	BRASS	端子電鍍材料鍍金GOLD FLASH
①	INSULATOR	1	PBT+30%G/F	BLACK/BLUE

KEM 奇速科技有限公司
Qi-Speed Technology CO., LTD.

產品名稱:
PRODUCT NAME

D-SUB 90° 母座 8.08mm

NO. POS	A±0.38	B±0.25	C±0.25
9PIN	30.80	24.99	16.33
15PIN	39.20	33.32	24.66
25PIN	53.04	47.04	38.38
37PIN	69.32	63.50	54.66

版本

修改事項

修改日期

單位: mm



比例:

公差: .X ±0.38

.XX ±0.25

.XXX ±0.15

日期: 2010/1/10

繪圖

DRAWING

設計

DESIGNED

審核

CHECKED BY

APPROVAL BY

JAMES

料號:KDSA5-XXF-1NX-X
PART NUMBER圖號:KDSA5-XXF-1NX-X-1
DRAWING NO

版本: REV. 0