

1. ELECTRICAL CHARACTERISTICS
 - 1-1. CURRENT RATING: 0.5 AMP
 - 1-2. VOLTAGE RATING: 40 V
 - 1-3. CONTACT RESISTANCE: 30MILLIOHMS MAX
 - 1-4. INSULATION RESISTANCE: 100M MIN. @ 500V DC
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE
2. MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE : 4.5KGF MAX.
 - 2-2. WITHDRAWING FORCE : 1KGF ~ 4KGF.
3. LIFE TEST: 10000 CYCLES
4. OPERATING TEMPERATURE: -25°C TO +85°C


Part No. :
KHD16- X 1012 X X 10

1. 黄铜
2. 铁材 (光面)
3. 铁材 (麻面)
4. S50C
5. 磷铜
6. 不锈钢

1. NICKEL PLATED
2. GOLD FLASH PLATED
3. GOLD PLATED 0.6u"
4. GOLD PLATED 足1u"
5. GOLD PLATED 足3u"
6. 鍍亚光銀 (连续鍍)

1. SELECTIVE GOLD 1u"
2. SELECTIVE GOLD 3u"
3. SELECTIVE GOLD 5u"
4. SELECTIVE GOLD 15u"
5. SELECTIVE GOLD 30u"
6. ALL GOLD

C	SHELL	1	C2680R-H Ni 50u"Min T=0.4mm PLATING ALL OVER
B	TERMINAL	19	C2680R-H,T=0.2±0.05mm
A	HOUSING	1	LCP E130i UL94V-0 BLACK
NO	PART NAME	QTY	MATERIAL PLATING & COLOR



KEm 奇速科技有限公司
Qi-Speed Technology CO., LTD.

產品名稱:
PRODUCT NAME

HDMI A版 侧插式A款成品两K脚两直脚
两K脚边距7.80 针长2.3 端子半金雾锡1u"

單位: mm 

比例：

公差：	.X	±0.38
	.XX	±0.25
	.XXX	±0.13

日期： 2021/3/25

繪圖
DRAWING

設計
DESIGNED

审核	核准
CHECKED BY	APPROVAL BY

料號:KHD16-X1012XX10
PART NUMBER

圖號:KHD16-X1012XX10-1
DRAWING NO

版本: REV. 0

版本

修改事項

修改日期